



## Pigment FL

Pigment for tinting MB FL 2K

Colour	Availability	
	Quantity per pallet	24000
	<b>Size / Quantity</b>	<b>20 ml</b>
	Type of container	Plastic bottle
	Container code	01
	<b>Art. no.</b>	
black	2863	■
white	2864	■

Application rate Depending on requirements and desired colour (max. 1.2% of total mass)

Colour variants:

Light grey: add 60 ml Pigment FL white per 10 kg MB FL 2K

Stone grey: add 20 ml Pigment FL black per 10 kg MB FL 2K

Anthracite: add 40 ml Pigment FL black per 10 kg MB FL 2K

Range of use ■ Tinting grout made from MB FL 2K

Property profile

- Very high pigment content
- Good flow properties
- Free from additives containing alkylphenols (APEO)

Characteristic data of the product

pH value	Approx. 7.5
Density	Art. 2863 black = approx. 2.36 g/cm <sup>3</sup> Art. 2864 white = approx. 1.80 g/cm <sup>3</sup>


The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Directions

- Conditions for use  
Temperature of the material, air and substrate: from min. +5 °C to max. +25 °C.

Add the required quantity of pigment to the liquid component and mix using a suitable mixing tool.  
Loosen the powder component and add it in full to the liquid component.  
Mix for approx. 1 minute before suspending the mixing process to allow the air that has been stirred in to escape.  
Remove the powder adhering to the side.  
Mix again for 2 minutes.  
Keep the mixing tool near the bottom of the bucket while mixing.

Storage / Shelf life At least 36 months in unopened, original containers stored cool, dry and protected from frost.



Safety data / Regulations For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.